

## Pendiro EC 125

Article number: 81020312

### LIGHT TECHNOLOGY

|                      |             |
|----------------------|-------------|
| LED                  | COB         |
| Light colour         | SpecialMeat |
| Luminous flux        | 2260 lm     |
| System power         | 41 W        |
| Luminaire Efficiency | 55 lm/W     |
| Reflector            | Spot        |
| Beam angle           | 20°         |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Weight                    | 3.0 kg      |
| Protection rating . class | IP 20 . I   |
| Luminaire colour          | stratowhite |

### OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratowhite

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |       |             |
|-------|-------|-------------|
| 1.0 m | 0.31  | 13649.0     |
| 2.0 m | 0.62  | 3412.3      |
| 3.0 m | 0.93  | 1516.6      |
| 4.0 m | 1.24  | 853.1       |
| 5.0 m | 1.55  | 546.0       |
|       | Ø (m) | E0(0°) [lx] |

