

Pendiro EC 125

Article number: 81040119

LIGHT TECHNOLOGY

| | |
|----------------------|------------|
| LED | COB |
| Light colour | PearlWhite |
| Luminous flux | 2620 lm |
| System power | 23 W |
| Luminaire Efficiency | 112 lm/W |
| Reflector | OvalBasic |
| Beam angle | 60° x 40° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Weight | 3.0 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | stratoblack |

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, canopy sheet steel, powder-coated, luminaire head die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Height (m) | Beam Diameter (m) | Beam Area (m²) | Illuminance (lx) |
|------------|-------------------|----------------|------------------|
| 1.0 | 1.05 | 0.41 | 4079.8 |
| 2.0 | 2.10 | 0.82 | 1019.9 |
| 3.0 | 3.15 | 1.22 | 453.3 |
| 4.0 | 4.20 | 1.63 | 255.0 |
| 5.0 | 5.25 | 2.04 | 163.2 |

