

# Pendiro EC 125

Article number: 81040255

## LIGHT TECHNOLOGY

|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | 927       |
| Luminous flux        | 3850 lm   |
| System power         | 41 W      |
| Luminaire Efficiency | 94 lm/W   |
| Reflector            | OvalBasic |
| Beam angle           | 60° x 40° |

## LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Weight                    | 3.0 kg       |
| Protection rating . class | IP 20 . I    |
| Luminaire colour          | stratosilver |

## OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, canopy sheet steel, powder-coated, luminaire head die-cast aluminium, powder-coated, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

