

# Pendiro EC 125

Article number: 81060055

## LIGHT TECHNOLOGY

|                      |         |
|----------------------|---------|
| LED                  | COB     |
| Light colour         | 927     |
| Luminous flux        | 3270 lm |
| System power         | 34 W    |
| Luminaire Efficiency | 98 lm/W |
| Reflector            | Flood   |
| Beam angle           | 40°     |

## LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Weight                    | 2.7 kg       |
| Protection rating . class | IP 20 . III  |
| Luminaire colour          | stratosilver |

## OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratosilver, separate driver unit

76500076 driver unit, Fix Current, 220-240 V / 50-60 Hz, 850 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

