

Pendiro EC 125

Article number: 81070204

LIGHT TECHNOLOGY

LED	COB
Light colour	840
Luminous flux	5150 lm
System power	41 W
Luminaire Efficiency	125 lm/W
Reflector	OvalBasic
Beam angle	60° x 40°

LUMINAIRE

Weight	2.7 kg
Protection rating . class	IP 20 . III
Luminaire colour	stratoblack

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, stratoblack, separate driver unit

76500037 driver unit, Fix Current, 220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	1.05 0.41	8019.4
2.0 m	2.10 0.82	2004.8
3.0 m	3.15 1.22	891.0
4.0 m	4.20 1.63	501.2
5.0 m	5.25 2.04	320.8
	Ø (m)	E0(0°) [lx]

