

# Pendiro ID

Article number: 80650031

#### LIGHT TECHNOLOGY


LED COB
Light colour PearlWhite
Luminous flux 2460 lm
System power 23 W
Luminaire Efficiency 106 lm/W
Reflector Flood
Beam angle 44°

#### **LUMINAIRE**

Weight 0.7 kg
Protection rating . class IP 20 . III
Luminaire colour stratowhite

#### **OPTIONEEL**

RAL-colours, NCS colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry



| Ø120 |



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), , reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire housing die-cast aluminium, powder-coated, stratowhite, separate driver unit

#### 76500055 recessed canopy,

Mounting plate with accessories for recessed fitting, Connecting cable with plug

connection for driver unit (order separately), cover sheet steel, powder-coated, stratowhite

#### 76500034 driver unit, Fix Current,

220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse), Treiber für Deckeneinbau

## 76500039 driver unit, DALI,

220-240 V / 50-60 Hz, 600 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse), Treiber für Deckeneinbau DALI

76500099 canopy with multiadapter inclusive driver unit, 220-240 V / 50-60 Hz, 600 mA, up to 2.5 KV interference resistance, SELV, max. 95 pcs. / B16 luminaires per circuit (B16A fuse), cover sheet steel, powder-coated, stratoblack, Multiadapter DALI

### 76500100 canopy, inclusive DALI driver,

220-240 V / 50-60 Hz, 600 mA, up to 2.5 KV interference resistance, SELV, max. 95 pcs. / B16 luminaires per circuit (B16A fuse), cover sheet steel, powder-coated, stratoblack, Deckenanbau DALI

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

