

Pendiro ID

Article number: 80650032

LIGHT TECHNOLOGY


LED СОВ Light colour Fish-Seafood Luminous flux 1600 lm 2.3 W System power Luminaire Efficiency 69 lm/W Reflector Flood Beam angle 44°

LUMINAIRE

Weight 0.7 kg Protection rating . class IP 20 . III Luminaire colour stratowhite

OPTIONEEL

RAL-colours, NCS colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry





Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), , reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire housing die-cast aluminium, powder-coated, stratowhite

driver unit, Fix Current,

220-240 V / 50-60 Hz, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)


driver unit, DALI,


220-240 V / 50-60 Hz, with GST18/5-pin connector, incl. 5-conductor feedthrough wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500099 canopy with multiadapter inclusive driver unit, 220-240 V / 50-60 Hz, 600 mA, up to 2.5 KV interference resistance, SELV, max. 95 pcs. / B16 luminaires per circuit (B16A fuse), cover sheet steel, powder-coated, stratoblack

76500100 canopy, inclusive DALI driver,

220-240 V / 50-60 Hz, 600 mA, up to 2.5 KV interference resistance, SELV, max. 95 pcs. / B16 luminaires per circuit (B16A fuse), cover sheet steel, powder-coated, stratoblack





Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.













16.10.2025 www.baero.com