

# Pendiro ID

Article number: 80660007

#### LIGHT TECHNOLOGY


LED СОВ PearlWhite Light colour Luminous flux 1690 lm 15 W System power Luminaire Efficiency 107 lm/W Reflector OvalBasic Beam angle 40° x 60°

#### **LUMINAIRE**

0.7 kg Weight Protection rating . class IP 20 . III Luminaire colour stratoblack

## **OPTIONAL**

RAL-colours, NCS colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry




















Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, exchangeable reflector unit in highsheen black plastic, with glass cover, luminaire housing die-cast aluminium, powder-coated, stratoblack, separate driver unit

## 76500054 recessed canopy,

Mounting plate with accessories for recessed fitting, Connecting cable with

connection for driver unit (order separately), cover sheet steel, powder-coated, stratoblack

#### 76500050 driver unit, Fix Current,

220-240 V / 50-60 Hz, 400 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse), Treiber für Deckeneinbau

## 76500051 driver unit, DALI,

220-240 V / 50-60 Hz, 400 mA, with GST18/5-pin connector, incl. 5conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse), Treiber für Deckeneinbau DALI

76500061 canopy with multiadapter inclusive DALI driver unit, 220-240 V / 50-60 Hz, 400 mA, up to 2.5 KV interference resistance, SELV, max. 95 pcs. / B16 luminaires per circuit (B16A fuse), cover sheet steel, powder-coated, stratoblack, Multiadapter DALI

# 76500062 canopy inclusive DALI driver unit,

220-240 V / 50-60 Hz, 400 mA, up to 2.5 KV interference resistance, SELV, max. 95 pcs. / B16 luminaires per circuit (B16A fuse), cover sheet steel, powder-coated, stratoblack, Deckenanbau DALI

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

24.11.2024 www.baero.com