

Pendiro XR

Article number: 80790046

LIGHT TECHNOLOGY

| | |
|----------------------|------------|
| LED | COB |
| Light colour | PearlWhite |
| Luminous flux | 2400 lm |
| System power | 23 W |
| Luminaire Efficiency | 104 lm/W |
| Reflector | Flood |
| Beam angle | 44° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Weight | 1.0 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | stratoblack |

OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry (only luminaire head and holding arm)



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, luminaire head die-cast aluminium, powder-coated, stratoblack

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Height (m) | Beam Diameter (m) | Illuminance E0(0°) [lx] |
|------------|-------------------|-------------------------|
| 1.0 | 0.81 | 4223.0 |
| 2.0 | 1.62 | 1055.8 |
| 3.0 | 2.43 | 469.2 |
| 4.0 | 3.24 | 263.9 |
| 5.0 | 4.05 | 168.9 |

