

Pendiro XR

Article number: 80830029

LIGHT TECHNOLOGY


LED COB
Light colour BeColor
Luminous flux 1990 lm
System power 23 W
Luminaire Efficiency 87 lm/W
Reflector Flood
Beam angle 44°

LUMINAIRE

Weight 0.6 kg Luminaire colour stratowhite

OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry (only luminaire head and holding arm





Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, luminaire head die-cast aluminium, powdercoated, stratowhite, separate driver unit


76500034 driver unit, Fix Current,


220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500039 driver unit, DALI,

220-240 V / 50-60 Hz, 600 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.















www.baero.com 17.10.2025