

Intara CX

Article number: 51400017

LIGHT TECHNOLOGY


LED COB
Light colour BeColor
Luminous flux 2440 lm
System power 34 W
Luminaire Efficiency 72 lm/W
Reflector WallWash

LUMINAIRE

 $\begin{array}{lll} \mbox{Rotation angle} & 350^{\circ} \\ \mbox{Swivel angle} & +15^{\circ} / -15^{\circ} \\ \mbox{Weight} & 0.80 \ \mbox{kg} \\ \mbox{Protection rating . class} & \mbox{IP20 . III} \\ \mbox{Luminaire colour} & \mbox{white} \\ \end{array}$

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver





Recessed wallwasher with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with asymmetrical light distribution pattern, primary reflector and kick reflector 99% pure aluminium in MIRO-Silver®, attachment with kick reflector for light cone projection, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head designed as heat sink die-cast aluminium, black anodized, rotation angle 350°, swivel angle +15°/-15°, assembly ring die-cast aluminum, front ring and trim in plastic, plastic clamp spring for ceiling attachment, white, separate driver unit


76500076 driver unit, Fix Current,

220-240 V / 50-60 Hz, 850 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500077 driver unit, DALI,

220-240 V / 50-60 Hz, 850 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

















www.baero.com 10.10.2025