

Intara EC 125

Article number: 51190051

LIGHT TECHNOLOGY


| | |
|----------------------|-----------|
| LED | COB |
| Light colour | 927 |
| Luminous flux | 2460 lm |
| System power | 23 W |
| Luminaire Efficiency | 105 lm/W |
| Reflector | OvalBasic |
| Beam angle | 60° x 30° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Rotation angle | 170° |
| Swivel angle | 65° |
| Weight | 1.9 kg |
| Protection rating . class | IP 20 . III |
| Luminaire colour | stratoblack |

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Semi-recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, rotation angle 170°, swivel angle 65°, mounting frame sheet steel, lightproof, stratoblack, separate driver unit

76500034 driver unit, Fix Current, 220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500039 driver unit, DALI, 220-240 V / 50-60 Hz, 600 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Distance (m) | Beam Diameter (m) | Illuminance (lx) |
|--------------|-------------------|------------------|
| 1.0 | 1.05 | 3830.6 |
| 2.0 | 2.10 | 957.7 |
| 3.0 | 3.15 | 425.6 |
| 4.0 | 4.20 | 239.4 |
| 5.0 | 5.25 | 153.2 |

Ø (m) E0(0°) [lx]

