

## Intara ID

Article number: 50570025

## LIGHT TECHNOLOGY


LED СОВ Light colour 830 Luminous flux 2060 lm 15 W System power Luminaire Efficiency 130 lm/W Reflector Spot Beam angle 20°

## **LUMINAIRE**

350° Rotation angle 34° Swivel angle 1.2 kg Weight Protection rating . class IP 20. III stratowhite Luminaire colour

## **OPCJA**

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver





Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, fitting ring and cover sheet steel, rotation angle 350°, swivel angle 34°, patented swivel-tilt mechanism, luminaire housing die-cast aluminium, powder-coated, stratowhite, separate driver unit

76500050 driver unit, Fix Current,

220-240 V / 50-60 Hz, 400 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500051 driver unit, DALI,

220-240 V / 50-60 Hz, 400 mA, with GST18/5-pin connector, incl. 5conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

