

# Intara ID

Article number: 50590016

## LIGHT TECHNOLOGY


|                      |         |
|----------------------|---------|
| LED                  | COB     |
| Light colour         | 927     |
| Luminous flux        | 2310 lm |
| System power         | 23 W    |
| Luminaire Efficiency | 99 lm/W |
| Reflector            | Flood   |
| Beam angle           | 44°     |

## LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Rotation angle            | 350°         |
| Swivel angle              | 34°          |
| Weight                    | 1.2 kg       |
| Protection rating . class | IP 20 . III  |
| Luminaire colour          | stratosilver |

## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, fitting ring and cover sheet steel, rotation angle 350°, swivel angle 34°, patented swivel-tilt mechanism, luminaire housing die-cast aluminium, powder-coated, stratosilver, separate driver unit

76500034 driver unit, Fix Current,  
220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500039 driver unit, DALI,  
220-240 V / 50-60 Hz, 600 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.81 | 4064.7      |
| 2.0 m | 1.62 | 1016.2      |
| 3.0 m | 2.43 | 451.6       |
| 4.0 m | 3.24 | 254.0       |
| 5.0 m | 4.05 | 162.6       |
| Ø (m) |      | E0(0°) [lx] |

