

## Intara ID

Article number: 50590022

## LIGHT TECHNOLOGY


LED COB
Light colour GoldenBread
Luminous flux 2370 lm
System power 23 W
Luminaire Efficiency 103 lm/W
Reflector Flood
Beam angle 44°

## **LUMINAIRE**

Rotation angle 350°
Swivel angle 34°
Weight 1.2 kg
Protection rating . class IP 20 . III
Luminaire colour stratosilver

## **OPTIONAL**

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver





Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), , reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, fitting ring and cover sheet steel, rotation angle 350°, swivel angle 34°, patented swivel-tilt mechanism, luminaire housing die-cast aluminium, powder-coated, stratosilver, separate driver unit


76500034 driver unit, Fix Current,


220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500039 driver unit, DALI,

220-240 V / 50-60 Hz, 600 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to  $2.5~{\rm KV}$  interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



















www.baero.com 16.10.2025