

# Intara RD 164

Article number: 50680024

### LIGHT TECHNOLOGY

LED COB
Light colour PearlWhite
Luminous flux 3980 lm
System power 41W
Luminaire Efficiency 97 lm/W
Reflector Flood
Beam angle 30°


### **LUMINAIRE**

Rotation angle  $+175^{\circ}$  /  $-175^{\circ}$ Swivel angle  $+30^{\circ}$  /  $-30^{\circ}$ Weight 0.8kg without driver

Protection rating . class IP 20 . III Luminaire colour black

## OPCJA

RAL colours





Recessed luminaire with LED, rated life of the LED L80/B10 > 50000h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), axially symmetrical reflector with circular light distribution pattern, 99,99% pure aluminium, segmented and faceted, infinitely adjustable sheet steel luminaire housing, incl. glass cover, sheet metal powder coated, separate driver unit

## 76500037 driver unit, fix current

220-240 V / 50-60 Hz, 1050 mA, with GST18/3-pin connector, incl. 3-conductor feed-through wiring, camera-compatible, up to  $2.5~{\rm KV}$  interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

## 76500042 driver unit, DALI

220-240 V / 50-60 Hz, 1050 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, up to 2.5 KV interference resistance, SELV, max. 52 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

