

# Intara RD 165

Article number: 51090107

## LIGHT TECHNOLOGY

|                      |             |
|----------------------|-------------|
| LED                  | COB         |
| Light colour         | SpecialMeat |
| Luminous flux        | 2260 lm     |
| System power         | 41 W        |
| Luminaire Efficiency | 55 lm/W     |
| Reflector            | Flood       |
| Beam angle           | 40°         |

## LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Swivel angle              | 2 x 25°      |
| Weight                    | 0.9 kg       |
| Protection rating . class | IP 20 . III  |
| Luminaire colour          | stratosilver |

## OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle +25°/-25°, luminaire housing sheet steel, powder-coated, stratosilver, separate driver unit

76500037 driver unit, Fix Current, 220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

76500042 driver unit, DALI, 220-240 V / 50-60 Hz, 1050 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.73 | 4487.4      |
| 2.0 m | 1.46 | 1121.9      |
| 3.0 m | 2.19 | 498.6       |
| 4.0 m | 2.92 | 280.5       |
| 5.0 m | 3.65 | 179.5       |
| Ø (m) |      | E0(0°) [lx] |

