

Intara RD 165

Article number: 51100114

LIGHT TECHNOLOGY


LED COB
Light colour PearlWhite
Luminous flux 4450 lm
System power 47 W
Luminaire Efficiency 94 lm/W
Reflector OvalBasic
Beam angle 60° x 30°

LUMINAIRE

 $\begin{array}{lll} \text{Swivel angle} & 2 \times 25^{\circ} \\ \text{Weight} & 0.9 \text{ kg} \\ \text{Protection rating . class} & \text{IP 20 . III} \\ \text{Luminaire colour} & \text{stratowhite} \\ \end{array}$

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver





Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle +25°/-25°, luminaire housing sheet steel, powdercoated, stratowhite, separate driver unit

driver unit, Fix Current,

220-240 V / 50-60 Hz, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

driver unit, DALI,

220-240 V / 50-60 Hz, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to $2.5~{\rm KV}$ interference resistance, SELV, max. $30~{\rm luminaires}$ per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

