

Intara RD 165

Article number: 51110051

LIGHT TECHNOLOGY


LED COB
Light colour 927
Luminous flux 4250 lm
System power 47 W
Luminaire Efficiency 89 lm/W
Reflector Spot
Beam angle 20°

LUMINAIRE

 $\begin{array}{lll} \text{Swivel angle} & 2 \times 25^{\circ} \\ \text{Weight} & 0.9 \text{ kg} \\ \text{Protection rating . class} & \text{IP 20 . III} \\ \text{Luminaire colour} & \text{stratoblack} \\ \end{array}$

OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver





Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle +25°/-25°, luminaire housing sheet steel, powder-coated, stratoblack, separate driver unit

76500086 driver unit, Fix Current, 220-240 V / 50-60 Hz, 1200 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500087 driver unit, DALI,

220-240 V / 50-60 Hz, 1200 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

