

# Intara RD 165

Article number: 51110111

## LIGHT TECHNOLOGY

|                      |              |
|----------------------|--------------|
| LED                  | COB          |
| Light colour         | Fish-Seafood |
| Luminous flux        | 2900 lm      |
| System power         | 41 W         |
| Luminaire Efficiency | 71lm/W       |
| Reflector            | Spot         |
| Beam angle           | 20°          |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Swivel angle              | 2 x 25°     |
| Weight                    | 0.9 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | stratowhite |

## OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle +25°/-25°, luminaire housing sheet steel, powder-coated, stratowhite, separate driver unit

76500037 driver unit, Fix Current,  
220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

76500042 driver unit, DALI,  
220-240 V / 50-60 Hz, 1050 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

