

# Intara RD 190

Article number: 51030002

## LIGHT TECHNOLOGY


|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 830      |
| Luminous flux        | 3180 lm  |
| System power         | 23 W     |
| Luminaire Efficiency | 136 lm/W |
| Reflector            | Flood    |
| Beam angle           | 40°      |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Rotation angle            | 170°        |
| Swivel angle              | 2 x 30°     |
| Weight                    | 1.0 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | stratoblack |

## OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 170°, swivel angle +30°/-30°, luminaire housing sheet steel, powder-coated, stratoblack, separate driver unit

76500034 driver unit, Fix Current, 220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500039 driver unit, DALI, 220-240 V / 50-60 Hz, 600 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.73 | 6314.2      |
| 2.0 m | 1.46 | 1578.5      |
| 3.0 m | 2.19 | 701.6       |
| 4.0 m | 2.92 | 394.6       |
| 5.0 m | 3.65 | 252.6       |
| Ø (m) |      | E0(0°) [lx] |

