

# Intara RD 190

Article number: 51130055

## LIGHT TECHNOLOGY

|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | 927       |
| Luminous flux        | 4250 lm   |
| System power         | 47 W      |
| Luminaire Efficiency | 89 lm/W   |
| Reflector            | OvalBasic |
| Beam angle           | 60° x 30° |

## LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Rotation angle            | 170°         |
| Swivel angle              | 2 x 30°      |
| Weight                    | 1.3 kg       |
| Protection rating . class | IP 20 . III  |
| Luminaire colour          | stratosilver |

## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 170°, swivel angle +30°/-30°, luminaire housing sheet steel, powder-coated, stratosilver, separate driver unit

76500086 driver unit, Fix Current, 220-240 V / 50-60 Hz, 1200 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500087 driver unit, DALI, 220-240 V / 50-60 Hz, 1200 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |             |        |
|-------|-------------|--------|
| 1.0 m | 1.05 0.41   | 6617.9 |
| 2.0 m | 2.10 0.82   | 1654.5 |
| 3.0 m | 3.15 1.22   | 735.3  |
| 4.0 m | 4.20 1.63   | 413.6  |
| 5.0 m | 5.25 2.04   | 264.7  |
| Ø (m) | E0(0°) [lx] |        |

