BÄRO
Retail
Lighting

# Intara SQ 174

Article number: 50660036

## LIGHT TECHNOLOGY

| | |
|---|---|
| LED | COB |
| Light colour | PearlWhite |
| Luminous flux | 3520 lm |
| System power | 41 W |
| Luminaire Efficiency | 86 lm/W |
| Reflector | Flood |
| Beam angle | 30° |

## LUMINAIRE

| | |
|---|---|
| Swivel angle | +30° / -30° |
| Weight | 1.1 kg |
| Protection rating . class | IP 20 . III |
| Luminaire colour | stratowhite |

## OPCJA

RAL colours



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, cardanic, swivel angle +30°/-30°, luminaire housing sheet steel, powder-coated, stratowhite, separate driver unit

76500037 driver unit, fix current
220-240 V / 50-60 Hz, 1050 mA, with GST18/3-pin connector, incl. 3-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

76500042 driver unit, DALI
220-240 V / 50-60 Hz, 1050 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 52 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.