

Intara SQ 175

Article number: 51070003

LIGHT TECHNOLOGY


| | |
|----------------------|-----------|
| LED | COB |
| Light colour | 835 |
| Luminous flux | 4260 lm |
| System power | 34 W |
| Luminaire Efficiency | 127 lm/W |
| Reflector | OvalBasic |
| Beam angle | 60° x 30° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Swivel angle | 30° |
| Weight | 1.9 kg |
| Protection rating . class | IP 20 . III |
| Luminaire colour | stratoblack |

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle 30°, luminaire housing sheet steel, powder-coated, stratoblack, separate driver unit

76500076 driver unit, Fix Current, 220-240 V / 50-60 Hz, 850 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500077 driver unit, DALI, 220-240 V / 50-60 Hz, 850 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Height (m) | Beam Diameter (m) | Illuminance E0(0°) [lx] |
|------------|-------------------|-------------------------|
| 1.0 m | 1.05 0.41 | 6633.5 |
| 2.0 m | 2.10 0.82 | 1658.4 |
| 3.0 m | 3.15 1.22 | 737.1 |
| 4.0 m | 4.20 1.63 | 414.6 |
| 5.0 m | 5.25 2.04 | 265.3 |

