

## Intara SQ 175

Article number: 51070107

### LIGHT TECHNOLOGY

|                      |             |
|----------------------|-------------|
| LED                  | COB         |
| Light colour         | SpecialMeat |
| Luminous flux        | 1640 lm     |
| System power         | 28 W        |
| Luminaire Efficiency | 60 lm/W     |
| Reflector            | OvalBasic   |
| Beam angle           | 60° x 30°   |

### LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Swivel angle              | 30°          |
| Weight                    | 1.9 kg       |
| Protection rating . class | IP 20 . III  |
| Luminaire colour          | stratosilver |

### OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle 30°, luminaire housing sheet steel, powder-coated, stratosilver, separate driver unit

76500035 driver unit, Fix Current, 220-240 V / 50-60 Hz, 700 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |            |        |
|-------|------------|--------|
| 1.0 m | 1.05 0.41  | 2554.0 |
| 2.0 m | 2.10 0.82  | 639.0  |
| 3.0 m | 3.15 1.23  | 284.0  |
| 4.0 m | 4.20 1.64  | 160.0  |
| 5.0 m | 5.25 2.05  | 103.0  |
| Ø (m) | E0(0°)(lx) |        |

