BÄRO
Retail
Lighting

# Intara SQ 175

Article number: 51340002

## LIGHT TECHNOLOGY

| | |
|---|---|
| LED | COB |
| Light colour | 835 |
| Luminous flux | 3460 lm |
| System power | 28 W |
| Luminaire Efficiency | 143 lm/W |
| Reflector | WallBeam |

## LUMINAIRE

| | |
|---|---|
| Swivel angle | 30° |
| Weight | 1.8 kg |
| Protection rating . class | IP 20 . III |
| Luminaire colour | stratoblack |

## OPCJA

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with asymmetrical light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle 30°, luminaire housing sheet steel, powder-coated, stratoblack, separate driver unit

76500035 driver unit, Fix Current,
220-240 V / 50-60 Hz, 700 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500040 driver unit, DALI,
220-240 V / 50-60 Hz, 700 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.