

Intara XR

Article number: 50870012

LIGHT TECHNOLOGY


LED COB
Light colour PearlWhite
Luminous flux 1500 lm
System power 15 W
Luminaire Efficiency 110 lm/W
Reflector Spot
Beam angle 20°

LUMINAIRE

 $\begin{array}{lll} \text{Swivel angle} & +25^{\circ}\,/\,\text{-}25^{\circ} \\ \text{Weight} & 0.69 \text{ kg} \\ \text{Protection rating . class} & \text{IP 20 . II} \\ \text{Luminaire colour} & \text{stratosilver} \end{array}$

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver





Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle, swivel angle +25° / -25°, stratosilver,

Inclusiv fix conected driver unit 220-240 V~ / 50-60 Hz, max. 36 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

