

## Intara XR

Article number: 50870047

### LIGHT TECHNOLOGY


|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | PearlWhite |
| Luminous flux        | 3150 lm    |
| System power         | 34 W       |
| Luminaire Efficiency | 93 lm/W    |
| Reflector            | Spot       |
| Beam angle           | 20°        |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Swivel angle              | +25°/-25°   |
| Weight                    | 0.69 kg     |
| Protection rating . class | IP 20 . II  |
| Luminaire colour          | stratoblack |

### OPTIONEEL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle , swivel angle +25°/-25°, stratoblack,

Inclusiv fix connected driver unit  
220-240 V~ / 50-60 Hz, max. 18 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.34 | 19166.5     |
| 2.0 m | 0.68 | 4791.6      |
| 3.0 m | 1.02 | 2129.6      |
| 4.0 m | 1.36 | 1197.9      |
| 5.0 m | 1.70 | 766.7       |
| Ø (m) |      | E0(0°) [lx] |

