

## Intara XR

Article number: 50870063

## LIGHT TECHNOLOGY


LED COB
Light colour BeCool
Luminous flux 2760 lm
System power 34 W
Luminaire Efficiency 81 lm/W
Reflector Spot
Beam angle 20°

## **LUMINAIRE**

Swivel angle +25°/-25°
Weight 0.69 kg
Protection rating . class IP 20 . II
Luminaire colour stratowhite

## **OPTIONEEL**

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver





Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle, swivel angle +25°/-25°, stratowhite,

Inclusiv fix conected driver unit 220-240 V~ / 50-60 Hz, max. 18 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

