

Intara XR

Article number: 50880052

LIGHT TECHNOLOGY

LED	COB
Light colour	835
Luminous flux	3830 lm
System power	34 W
Luminaire Efficiency	116 lm/W
Reflector	Medium
Beam angle	24°

LUMINAIRE

Swivel angle	+25° / -25°
Weight	0.69 kg
Protection rating . class	IP 20 . II
Luminaire colour	stratosilver

OPTIONEEL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle , swivel angle +25° / -25°, stratosilver,

Inclusiv fix connected driver unit
220-240 V~ / 50-60 Hz, max. 18 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.45	13275.4
2.0 m	0.90	3318.8
3.0 m	1.35	1475.0
4.0 m	1.80	829.7
5.0 m	2.25	531.0
Ø (m)		E0(0°) [lx]

