

Intara XR

Article number: 50900027

LIGHT TECHNOLOGY

| | |
|----------------------|-----------|
| LED | COB |
| Light colour | BeColor |
| Luminous flux | 2020 lm |
| System power | 23 W |
| Luminaire Efficiency | 88 lm/W |
| Reflector | OvalBasic |
| Beam angle | 60° x 40° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Swivel angle | +25° / -25° |
| Weight | 0.69 kg |
| Protection rating . class | IP 20 . II |
| Luminaire colour | stratoblack |

OPTIONEEL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, die-cast aluminium, powder-coated, rotation angle , swivel angle +25° / -25°, stratoblack,

Inclusiv fix connected driver unit
220-240 V~ / 50-60 Hz, max. 18 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Height (m) | Beam Diameter (m) | Beam Area (m²) | Illuminance (lx) |
|------------|-------------------|----------------|------------------|
| 1.0 | 1.14 | 0.76 | 2221.2 |
| 2.0 | 2.28 | 1.53 | 555.3 |
| 3.0 | 3.42 | 2.29 | 246.8 |
| 4.0 | 4.56 | 3.05 | 138.8 |
| 5.0 | 5.70 | 3.82 | 88.8 |

Ø (m) E0(0°) [lx]

