

## Intara XR

Article number: 50690018

### LIGHT TECHNOLOGY

|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | BeCool     |
| Luminous flux        | 1060 lm    |
| System power         | 15 W       |
| Luminaire Efficiency | 71 lm/W    |
| Reflector            | NarrowSpot |
| Beam angle           | 10°        |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Rotation angle            | 400°        |
| Swivel angle              | +85° / -85° |
| Weight                    | 0.65 kg     |
| Protection rating . class | IP 20 . II  |
| Luminaire colour          | stratowhite |

### OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Semi-recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle 400°, swivel angle +85° / -85°, stratowhite, separate driver unit

76500050 driver unit, Fix Current, 220-240 V / 50-60 Hz, 400 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500051 driver unit, DALI, 220-240 V / 50-60 Hz, 400 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Distance (m) | Beam diameter Ø (m) | Illuminance E0(0°) (lx) |
|--------------|---------------------|-------------------------|
| 1.0 m        | 0.18                | 21526.3                 |
| 2.0 m        | 0.36                | 5381.6                  |
| 3.0 m        | 0.54                | 2391.8                  |
| 4.0 m        | 0.72                | 1345.4                  |
| 5.0 m        | 0.90                | 861.1                   |

