

## Intara XR

Article number: 50780010

### LIGHT TECHNOLOGY

|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | 840       |
| Luminous flux        | 4590 lm   |
| System power         | 41 W      |
| Luminaire Efficiency | 112 lm/W  |
| Reflector            | OvalBasic |
| Beam angle           | 60° x 40° |

### LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Rotation angle            | 400°         |
| Swivel angle              | +85°/-85°    |
| Weight                    | 0.65 kg      |
| Protection rating . class | IP 20 . II   |
| Luminaire colour          | stratosilver |

### OPTIONEEL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Semi-recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, die-cast aluminium, powder-coated, rotation angle 400°, swivel angle +85°/-85°, stratosilver, potentiometer to adjust the brightness, separate driver unit

76500109 driver unit, Fix Current, 220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |           |             |
|-------|-----------|-------------|
| 1.0 m | 1.14 0.76 | 5047.2      |
| 2.0 m | 2.28 1.53 | 1261.8      |
| 3.0 m | 3.42 2.29 | 560.8       |
| 4.0 m | 4.56 3.05 | 315.4       |
| 5.0 m | 5.70 3.82 | 201.9       |
| Ø (m) |           | E0(0°) [lx] |

