

## beledi XS

Article number: 70610715

### LIGHT TECHNOLOGY

|                      |            |
|----------------------|------------|
| LED                  | SMD linear |
| Light colour         | 830        |
| Luminous flux        | 4000 lm    |
| System power         | 27 W       |
| Luminaire Efficiency | 148 lm/W   |
| Reflector            | MediumBeam |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 3.2 kg    |
| Protection rating . class | IP 40 . I |
| Luminaire colour          | black     |

### OPTIONEEL


Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, black

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |            |        |
|-------|------------|--------|
| 1.0 m | 1.57 1.51  | 2873.0 |
| 2.0 m | 3.14 3.02  | 718.0  |
| 3.0 m | 4.71 4.53  | 319.0  |
| 4.0 m | 6.28 6.04  | 180.0  |
| 5.0 m | 7.85 7.55  | 115.0  |
| Ø (m) | E0(0°)(lx) |        |

