

## beledi XS

Article number: 70620707

### LIGHT TECHNOLOGY

|                      |            |
|----------------------|------------|
| LED                  | SMD linear |
| Light colour         | 830        |
| Luminous flux        | 4800 lm    |
| System power         | 32 W       |
| Luminaire Efficiency | 150 lm/W   |
| Reflector            | NarrowBeam |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 3.2 kg    |
| Protection rating . class | IP 40 . I |
| Luminaire colour          | black     |

### OPTIONEEL


Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, black

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Distance (m) | Beam Diameter (m) | Beam Angle (°) | Intensity (lx) |
|--------------|-------------------|----------------|----------------|
| 1.0          | 1.43              | 0.62           | 5584.0         |
| 2.0          | 2.86              | 1.24           | 1396.0         |
| 3.0          | 4.29              | 1.86           | 620.0          |
| 4.0          | 5.72              | 2.48           | 349.0          |
| 5.0          | 7.15              | 3.10           | 223.0          |

