

## beledi XS

Article number: 70660404

### LIGHT TECHNOLOGY


|                      |               |
|----------------------|---------------|
| LED                  | SMD linear    |
| Light colour         | 830           |
| Luminous flux        | 6000 lm       |
| System power         | 44.5 W        |
| Luminaire Efficiency | 135 lm/W      |
| Reflector            | Xtra WideBeam |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 3.2 kg    |
| Protection rating . class | IP 40 . I |
| Luminaire colour          | silver    |

### OPTIONAL


Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, silver

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |             |        |
|-------|-------------|--------|
| 1.0 m | 2.94 2.48   | 1942.0 |
| 2.0 m | 5.88 4.96   | 485.0  |
| 3.0 m | 8.82 7.44   | 216.0  |
| 4.0 m | 11.76 9.92  | 121.0  |
| 5.0 m | 14.70 12.40 | 78.0   |
| Ø (m) | E0(0°)(lx)  |        |

