

## beledi XS

Article number: 70670710

### LIGHT TECHNOLOGY


|                      |            |
|----------------------|------------|
| LED                  | SMD linear |
| Light colour         | 830        |
| Luminous flux        | 9000 lm    |
| System power         | 73.5 W     |
| Luminaire Efficiency | 122 lm/W   |
| Reflector            | SoftBeam   |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 3.2 kg    |
| Protection rating . class | IP 40 . I |
| Luminaire colour          | black     |

### OPTIONAL


Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, black

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |             |            |
|-------|-------------|------------|
| 1.0 m | 2.24 2.10   | 3354.0     |
| 2.0 m | 4.48 4.20   | 838.0      |
| 3.0 m | 6.72 6.30   | 373.0      |
| 4.0 m | 8.96 8.40   | 210.0      |
| 5.0 m | 11.20 10.50 | 134.0      |
| Ø (m) |             | E0(0°)(lx) |

