

## beledi XS

Article number: 70670821

### LIGHT TECHNOLOGY

|                      |            |
|----------------------|------------|
| LED                  | SMD linear |
| Light colour         | 840        |
| Luminous flux        | 6000 lm    |
| System power         | 43 W       |
| Luminaire Efficiency | 140 lm/W   |
| Reflector            | SoftBeam   |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 3.2 kg    |
| Protection rating . class | IP 40 . I |
| Luminaire colour          | black     |

### OPCJA


Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, black

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |             |            |
|-------|-------------|------------|
| 1.0 m | 2.24 2.10   | 2515.0     |
| 2.0 m | 4.48 4.20   | 629.0      |
| 3.0 m | 6.72 6.30   | 279.0      |
| 4.0 m | 8.96 8.40   | 157.0      |
| 5.0 m | 11.20 10.50 | 101.0      |
|       | Ø (m)       | E0(0°)(lx) |

