

beledi XS

Article number: 70680214

LIGHT TECHNOLOGY

| | |
|----------------------|------------|
| LED | SMD linear |
| Light colour | 840 |
| Luminous flux | 4000 lm |
| System power | 28.5 W |
| Luminaire Efficiency | 140 lm/W |
| Reflector | SoftBeam+ |

LUMINAIRE

| | |
|---------------------------|-----------|
| Weight | 3.2 kg |
| Protection rating . class | IP 40 . I |
| Luminaire colour | white |

OPTIONAL

Mounting Accessories



Light band with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, reflector with homogeneous light distribution pattern, lens optics made of PMMA, luminaire insert sheet steel, powder-coated, white

driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Height (m) | Beam Diameter (m) | Beam Area (m²) | Beam Diameter (m) | Beam Area (m²) |
|------------|-------------------|----------------|-------------------|----------------|
| 1.0 | 0.36 | 0.41 | 1.288 | 1.288 |
| 2.0 | 0.72 | 1.63 | 2.576 | 3.220 |
| 3.0 | 1.08 | 3.65 | 3.864 | 14.73 |
| 4.0 | 1.44 | 6.55 | 5.152 | 26.56 |
| 5.0 | 1.80 | 10.21 | 6.440 | 41.65 |

Ø (m) E0(0°)(lx)

