

Intara TX

Article number: 50810004

LIGHT TECHNOLOGY

| | |
|----------------------|-----------|
| LED | SMD-Board |
| Light colour | 830 |
| Luminous flux | 8470 lm |
| System power | 64 W |
| Luminaire Efficiency | 132 lm/W |
| Reflector | WideFlood |
| Beam angle | 60° |

LUMINAIRE

| | |
|---------------------------|------------|
| Weight | 3.2 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | matt white |

OPTIONAL

Accessories for feed-through wiring,
cover stripes



Lay in luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), wide, homogeneous light distribution pattern, TIR-lens made of PMMA, luminaire housing sheet steel, powder-coated, matt white

Driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240 V~ / 50-60 Hz, max. 16 Pcs. luminaires per circuit (B16A fuse).

Order ceiling attachment with visible supporting profile separately:
5080Z600 B-Set for Ceiling Systems 600
5080Z625 B-Set for Ceiling Systems 625

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-------------|------------------|
| 1 | 1,16 . 1,10 | 893,8 |
| 2 | 2,32 . 2,20 | 223,4 |
| 3 | 3,48 . 3,30 | 99,3 |
| 4 | 4,64 . 4,40 | 55,9 |
| 5 | 5,80 . 5,50 | 35,8 |
| h (m) | Ø (m) | E0 (0°) (lx/klm) |

