

Intara TX

Article number: 50820004

LIGHT TECHNOLOGY

| | |
|----------------------|----------------|
| LED | SMD-Board |
| Light colour | 830 |
| Luminous flux | 6560 lm |
| System power | 49 W |
| Luminaire Efficiency | 134 lm/W |
| Reflector | Xtra WideFlood |
| Beam angle | 90° |

LUMINAIRE

| | |
|---------------------------|------------|
| Weight | 3.2 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | matt white |

OPTIONEEL

Accessories for feed-through wiring,
cover stripes



Lay in luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), extra wide, homogeneous light distribution pattern, TIR-lens made of PMMA, luminaire housing sheet steel, powder-coated, matt white


Driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240 V~ / 50-60 Hz, max. 16 Pcs. luminaires per circuit (B16A fuse).

Order ceiling attachment with visible supporting profile separately:

5080Z600 B-Set for Ceiling Systems 600

5080Z625 B-Set for Ceiling Systems 625

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| h (m) | Ø (m) | E0 (0°) (lx/klm) |
|-------|---------------|------------------|
| 1 | 2,63 . 2,50 | 382,5 |
| 2 | 5,26 . 5,00 | 96,6 |
| 3 | 7,89 . 7,50 | 42,5 |
| 4 | 10,52 . 10,00 | 23,9 |
| 5 | 13,15 . 12,50 | 15,3 |

