

## Intara TX

Article number: 50830005

### LIGHT TECHNOLOGY

|                      |                      |
|----------------------|----------------------|
| LED                  | SMD-Board            |
| Light colour         | 835                  |
| Luminous flux        | 8420 lm              |
| System power         | 60 W                 |
| Luminaire Efficiency | 140 lm/W             |
| Reflector            | doppelt asymmetrisch |
| Beam angle           | 2 x 20°              |

### LUMINAIRE

|                           |            |
|---------------------------|------------|
| Weight                    | 3.2 kg     |
| Protection rating . class | IP 20 . I  |
| Luminaire colour          | matt white |

### OPTIONAL

Accessories for feed-through wiring,  
cover stripes



Lay in luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern, lens made of PMMA, luminaire housing sheet steel, powder-coated, matt white

Driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240 V~ / 50-60 Hz, max. 16 Pcs. luminaires per circuit (B16A fuse).

Order ceiling attachment with visible supporting profile separately:  
5080Z600 B-Set for Ceiling Systems 600  
5080Z625 B-Set for Ceiling Systems 625

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

