

## Ontero TX

Article number: 21380004

## LIGHT TECHNOLOGY


LED SMD-Board Light colour 830

Luminous flux5630 - 9950 lmSystem power38 W - 72 WLuminaire Efficiency148 lm/W - 138 lm/W

Reflector WideFlood Beam angle 60°

## **LUMINAIRE**

Rotation angle 330°
Weight 3.1 kg
Protection rating . class IP 20 . I
Luminaire colour matt white







Surface-mounted luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern, TIR-lens made of PMMA, Driver with power selection via DIP switch, 8 possible levels: 38 W (5410 lm), 42 W (6000 lm), 47 W (6550 lm), 52 W (7120 lm), 57 W (7680 lm), 62W (8210 lm), 67 W (8750 lm), 72 W (9290 lm), 62 Watt preselected, rotation angle 330°, luminaire housing sheet steel, powder-coated, matt white,

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse), DIP-Switch 38W-72W (default 53W), temperature protection

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



















www.baero.com 21.10.2025