

Ontero TX

Article number: 21380006

LIGHT TECHNOLOGY


LED SMD-Board Light colour 840

Luminous flux 6010 - 10620 lm System power 38 W - 72 W Luminaire Efficiency 158 lm/W - 148 lm/W

Reflector WideFlood Beam angle 60°

LUMINAIRE

Rotation angle 330°
Weight 3.1 kg
Protection rating . class IP 20 . I
Luminaire colour matt white







Surface-mounted luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern, TIR-lens made of PMMA, Driver with power selection via DIP switch, 8 possible levels: 38 W (5770 lm), 42 W (6400 lm), 47 W (6990 lm), 52 W (7600 lm), 57 W (8200 lm), 62W (8760 lm), 67 W (9340 lm), 72 W (9910 lm), 62 Watt preselected, rotation angle 330°, luminaire housing sheet steel, powder-coated, matt white,

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse), DIP-Switch 38W-72W (default 53W), temperature protection

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



















www.baero.com 22.10.2025