

Ontero TX

Article number: 21390002

LIGHT TECHNOLOGY


LED SMD-Board Light colour 835

Luminous flux 5730 - 10110 lm
System power 38 W - 72 W
Luminaire Efficiency 151 lm/W - 140 lm/W
Reflector Xtra WideFlood

Beam angle 90°

LUMINAIRE

Rotation angle 330°
Weight 3.1 kg
Protection rating . class IP 20 . I
Luminaire colour matt black





Surface-mounted luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), extra wide, homogeneous light distribution pattern, TIR-lens made of PMMA, power selection via DIP switch, 8 possible levels: 38 W (5530 lm), 42 W (6130 lm), 47 W (6700 lm), 52 W (7280 lm), 57 W (7850 lm , preset), 62W (8390 lm), 67 W (8950 lm), 72 W (9490 lm), rotation angle 330°, luminaire housing sheet steel, powder-coated, matt black,

Multiadapter black, inclusive driver unit: 220-240 V~/50-60 Hz, max. 24 luminaires per circuit (B16A fuse), DIP-Switch 38W-72W (default 53W), temperature protection

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

