

Ontero TX

Article number: 21400008

LIGHT TECHNOLOGY

SMD-Board LED Light colour


Luminous flux 5920 - 10450 lm 38 W - 72 W System power Luminaire Efficiency 156 lm/W - 145 lm/W Reflector doppelt asymmetrisch

Beam angle 2 x 20°

LUMINAIRE

330° Rotation angle 3.1 kg Weight Protection rating . class IP20.I Luminaire colour matt silver

OPTIONEEL



Surface-mounted luminaire with LED, rated life of the LED L80/B50 > 50000h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern, lens made of PMMA, Driver with power selection via DIP switch, 8 possible levels: 38 W (5680 lm), 42 W (6300 lm), 47 W (6880 lm), 52 W (7480 lm), 57 W (8070 lm), 62W (8620 lm), 67 W (9190lm), 72 W (9750 lm), 62 Watt preselected, rotation angle 330°, luminaire housing sheet steel, powder-coated, matt silver,

×

inclusiv driver unit: 220-240 V~ / 50-60 Hz, DALI, max. 15 luminaires per circuit (B16A fuse), temperature protection

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

