

Pendiro TX

Article number: 80850003

LIGHT TECHNOLOGY

LED	SMD-Bord
Light colour	840
Luminous flux	7450 lm
System power	53 W
Luminaire Efficiency	141 lm/W
Reflector	WideFlood
Beam angle	60°

LUMINAIRE

Rotation angle	+165° / -165°
Weight	3.7 kg
Protection rating . class	IP 20 . I
Luminaire colour	matt black




Suspended luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), wide, homogeneous light distribution pattern, TIR-lens made of PMMA, luminaire housing sheet steel, powder-coated, matt black, power supply via suspension cables

Canopy with SELV driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240 V~ / 50-60 Hz, max. 16 Pcs. luminaires per circuit (B16A fuse), Steel sheet powder-coated

Order separately:

76500079 E-Set with Canopy, black
76500081 E-Set with Canopy, white
76500083 E-Set with Canopy, DALI, black
76500085 E-Set with Canopy, DALI, white
76500078 E-Set for 3-Ph Track, black
76500080 E-Set for 3-Ph Track, white
76500082 E-Set for 3-Ph Track, DALI, black
76500084 E-Set for 3-Ph Track, DALI, white

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1	1,16 . 1,10	893,8
2	2,32 . 2,20	223,4
3	3,48 . 3,30	99,3
4	4,64 . 4,40	55,9
5	5,80 . 5,50	35,8
h (m)	Ø (m)	E0 (0°) (lx/klm)

