

Pendiro TX

Article number: 80850004

LIGHT TECHNOLOGY

| | |
|----------------------|-----------|
| LED | SMD-Bord |
| Light colour | 830 |
| Luminous flux | 6630 lm |
| System power | 49 W |
| Luminaire Efficiency | 135 lm/W |
| Reflector | WideFlood |
| Beam angle | 60° |

LUMINAIRE

| | |
|---------------------------|---------------|
| Rotation angle | +165° / -165° |
| Weight | 3.7 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | matt white |



Suspended luminaire with LED, rated life of the LED L80/B50 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), wide, homogeneous light distribution pattern, TIR-lens made of PMMA, luminaire housing sheet steel, powder-coated, matt white, power supply via suspension cables

Canopy with SELV driver with adjustable system power in 8 steps (38 W to 64 W), choice by DIP-Switch, 220-240 V~ / 50-60 Hz, max. 16 Pcs. luminaires per circuit (B16A fuse), Steel sheet powder-coated

Order separately:

- 76500079 E-Set with Canopy, black
- 76500081 E-Set with Canopy, white
- 76500083 E-Set with Canopy, DALI, black
- 76500085 E-Set with Canopy, DALI, white
- 76500078 E-Set for 3-Ph Track, black
- 76500080 E-Set for 3-Ph Track, white
- 76500082 E-Set for 3-Ph Track, DALI, black
- 76500084 E-Set for 3-Ph Track, DALI, white

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-------------|------------------|
| 1 | 1,16 . 1,10 | 893,8 |
| 2 | 2,32 . 2,20 | 223,4 |
| 3 | 3,48 . 3,30 | 99,3 |
| 4 | 4,64 . 4,40 | 55,9 |
| 5 | 5,80 . 5,50 | 35,8 |
| h (m) | Ø (m) | E0 (0°) (lx/klm) |

