

# Ontero EC 125

Article number: 21080067

## LIGHT TECHNOLOGY


|                      |         |
|----------------------|---------|
| LED                  | COB     |
| Light colour         | 927     |
| Luminous flux        | 4250 lm |
| System power         | 47 W    |
| Luminaire Efficiency | 89 lm/W |
| Reflector            | Spot    |
| Beam angle           | 20°     |

## LUMINAIRE

|                           |              |
|---------------------------|--------------|
| Rotation angle            | 350°         |
| Swivel angle              | 210°         |
| Weight                    | 2.1 kg       |
| Protection rating . class | IP 20 . I    |
| Luminaire colour          | stratosilver |

## OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 350°, swivel angle 210°, luminaire housing die-cast aluminium, powder-coated, stratosilver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.31 | 25667.4     |
| 2.0 m | 0.62 | 6416.9      |
| 3.0 m | 0.93 | 2851.9      |
| 4.0 m | 1.24 | 1604.2      |
| 5.0 m | 1.55 | 1026.7      |
| Ø (m) |      | E0(0°) [lx] |

