

Ontero IC

Article number: 21450044

LIGHT TECHNOLOGY

| | |
|----------------------|---------|
| LED | COB |
| Light colour | Sun |
| Luminous flux | 1520 lm |
| System power | 23 W |
| Luminaire Efficiency | 66 lm/W |
| Reflector | Medium |
| Beam angle | 24° |

LUMINAIRE

| | |
|---------------------------|-------------|
| Rotation angle | 330° |
| Swivel angle | +/- 90° |
| Weight | 1.1 kg |
| Protection rating . class | IP 20 . II |
| Luminaire colour | stratoblack |

OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, OvalBeam lens or honeycomb louver, Casambi model on inquiry



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, chromaticity tolerance 3 SDCM (initial), LED hybrid technology, 3D silicone lens to reduce the proportion of scattered light, reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head die-cast aluminium, powder-coated, rotation angle 330°, swivel angle +/-90°, luminaire head/retention arm die-cast aluminium, stratoblack

In-Track-Adapter, Fix Current, black,
max. 50 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 0.44 | 5222.2 |
| 2.0 m | 0.88 | 1305.5 |
| 3.0 m | 1.32 | 580.2 |
| 4.0 m | 1.76 | 326.4 |
| 5.0 m | 2.20 | 208.9 |
| Ø (m) | | E0(0°) [lx] |

